

# PanAust process control strategy and implementation

PanAust Senior Advisor – Process Controls  
Dirk Baas

CEEC Mineral Processing and Innovation Workshop  
Energy Curves: New tools for energy efficiency




PANAUST

# The strategy



- Lift the role of the operator:
  - From setting individual loop setpoints
  - To monitoring the process and only intervening on exception
  - The expertise lies with the metallurgists
- Ensure the process is always running up against a constraint.
- Develop process control solutions that can be implemented at other operations





# The tactics

- Stabilise the plant beginning at the front end
  - Fix the instrumentation and apply good first principles control theory
- Improve the operator situational awareness
  - HMI graphics and alarming
- Identify the best process control solutions
  - Model based and predictive control solutions
  - Developed on the existing DCS platform (No fuzzy black boxes)
- All process automation models are verified against metallurgical first principles

# The crusher

- Added an encoder and implemented a dead time compensator on apron feeder
- This indirectly improved throughput
  - A consistent feed to CV02
  - CV02 is a 1.2km long conveyer
  - Reduced overloading
  - Reduced spillage
    - Often causing pull wire trips
  - Improved the availability of CV02

# The improvements at the crusher




- Increased throughput
- Reduced the excursions on the high end, increasing availability

# The SAG mill control

- Operate within the following constraints
  - SAG mill motor power and rotor current
  - SAG mill weight
  - SAG mill noise
  - CV04 pebble recycle conveyer
  - Down stream copper tonnes limit (Cleaner constraint of 18t/hr copper)
- Manipulated variables
  - SAG mill feedrate
  - SAG mill speed
  - SAG mill density






# The SAG Gain profile



This gain profile moves depending on SAG mill speed, power and noise

# The SAG Improvement

- SAG Mill Throughput increased by 4%
- The SAG Mill is controlled in a much tighter region.
- SAG Mill Control utilisation was 97% in June 2018.



Analysis was done in 2012, no further analysis has been conducted

# Operator situational awareness

- The operator is part of the control system
- Without situational awareness
  - The operator will be slower to respond
  - Be more likely to make the wrong decision
- HMI graphic colours must be meaningful
- Alarms must be informative to the operator
- This is a huge topic and will not be covered in detail



Grinding SP Mass Balance Run Hours

Lime Addition Control  
pH Control Ratio Control

TREND  
PV: 10.18 AI-4310  
AUT: 9.75 AI-4303  
RO Cond Tank pH: SV: 10.20  
Lime Plant: MV: 8.84 4.7 m3/h

Feed moisture, % wb: 5.0 %  
Requ'd %solid discharge: 68.0 %  
Cu-Metal Tonnes: 10.61 tph Cu  
Requ'd feed water flow: 1107 m3/h  
Sag mill feed water: 1103 m3/h












Water Supply  
Power High Limit: 12800 kW  
Feed High Limit: 2725 t/h  
Cu(t/h) Limit: 14.00 t/h  
Requ'd CV03 Feed: 2725 t/h

WEIGHT Ctrl  
MAN AUT CAS  
PV 2726 t/h  
SV 2725 t/h  
MV 167.9 %

CV-03  
77.1 %  
90.7 %  
89123336 tonnes  
Sagmill Trend  
Shift Tons Milled  
Mill Downtime Record

A I  
22-MA-002  
Ambient Temp: 34.9°C


Pebble conveyor CV-05  
3986622 t  
68.9 %  
CV05 Speed: AUT 34.8 Hz  
Reclaim CV-05 Detail  
Tramp Bunker




# Phu Kham Processing plant improvements achieved

- SAG mill and grinding circuit automation
  - 2012 SAG speed and feedrate automation
  - 2015 SAG noise analyser improves control
  - 2017 SAG motor constraints improve reliability
  - 2018 SAG density control – volumetric scanner on CV03
- Rougher automation
  - 2013 froth analysers control froth depth and airflow
  - 2015 mass recovery determined by feed grade
  - 2016 reagent automation
- Jameson cell, Cleaner 1, 2, 3 automation
  - 2015 Airflow and froth depth profiles adjusted to suit the grade
  - 2017 Concentrate grade setpoints of each cleaner bank automated
- The utilisation of the advanced automation exceeds 95%

# Phu Kham Operations - Throughput and recovery performance - April 2008 to January 2018



# Automating a new plant



- Define the high level process control objective.
  - The top of the hierarchy of control
- This determines the holistic and advanced control required
- Which leads to the stabilising and regulatory control needed.
- Finally, the instrumentation required to achieve the objective is identified

# Conclusion

- Process control requires a strategic approach
- The obvious improvements realised by reduced variation are:
  - Allowing the process to run closer to its constraints
    - Increases throughput, recovery and grades
    - Reduces unnecessary stress on the asset
- The understated benefits are:
  - The accuracy of metallurgical test work improves
  - Allowing the control model to be further improved
  - The plant availability increases

# Important notices

This presentation has been prepared solely for informational purposes and not as specific advice to any particular party or person. The information is based on publicly available information, internally developed data and other sources. No independent verification of those sources has been undertaken and where any opinion is expressed in this presentation it is based on the assumptions and limitations mentioned herein and is an expression of present opinion only. No warranties or representations can be made as to the origin, validity, accuracy, completeness, currency or reliability of the information. PanAust Limited (**Company**) disclaims and excludes all liability (to the extent permitted by law), for losses, claims, damages, demands, costs and expenses of whatever nature arising in any way out of or in connection with the information, its accuracy, completeness or by reason of reliance by any person on any of it. The Company does not have any obligation to advise any person if it becomes aware of any inaccuracy in, or omission from, the information contained in this presentation.